

**Product:** Pyreflect™ blanket

MATERIAL SAFETY DATA SHEET



### 1. Chemical Product and Company Identification

**Emergency Contact:** ADL Insulflex, Inc.

(address & emergency phone numbers - page 4)

Revised: June 2008 Chemical family: N/A

Formula: Proprietary mixture

Description: Aluminized Aramid/Fiberglass blend

# 2. Composition / Information on ingredients

Product Composition CAS Reg. No.	Approx. % Limit Values <b>VVt</b> .		
A. HAZARDOUS			
Aluminized Polyester Film Fabric Trade Secret (adhesive)	1.50 89.50 9.00	N/A N/A N/A	

#### 3. Hazards identification

Potential health effects:

Ingestion: None at normal temperatures Skin contact: None at normal temperatures Skin contact: None at normal temperatures Inhalation: None at normal temperatures

Medical conditions aggravated: None known Sub-chronic (Target organ) effects: None known Chronic effects/carcinogenic: None known Principle routes of exposure: None known

Other:

First aid procedures for inhalation: Inhalation of decomposition gases at extreme

high temperatures (over 400°F)—remove victim to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen.

Consult physician.

#### 4. First aid measures

Ingestion: Consult a physician Skin: Wash with soap and water.

Inhalation: Inhalation of decomposition gases at extreme high

temperatures (over 400°F) – remove victim to

fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen.

Consult physician.

In case of eye contact: Flush with water for 15 minutes and get medical

attention if irritation persists.

Note to physician: None known.

# 5. Fire fighting measures

Flash point: N/A
Flammable limits in air – upper % N/A
Sensitivity to mechanical impact: No

Extinguishing media: Naturally self-extinguishing. Material starts to

decompose at extreme high temperatures (over 400°F). The adhesive system is self-extinguishing and tends to smolder in the flame. The aluminized

polyester film starts to melt at about 400°F. Extinguish with water, chemical foam, dry

chemical, Co2 and/or smother.

Special fire fighting procedures: Wear self-contained breathing apparatus.

#### 6. Accidental release measures

Product is a solid.

# 7. Handling and storage

Precautions for handling and storage: Normal warehouse conditions. Avoid high temperatures and open flame.

#### 8. Exposure controls / Personal protection

Engineering controls: None known

Respiratory protection: Avoid breathing fibers or dust

Protective gloves:

Eye and face protection:

Other protective equipment:

None required

None required

Ventilation: Local exhaust ventilation (if needed) to maintain

appropriate airborne dust levels.

#### 9. Physical and chemical properties

N/A Boiling point: Vapor pressure: N/A Vapor density: N/A Freezing point: N/A Melting point: N/A Physical state: Solid None Odor: % volatile by volume N/A pH: N/A

Specific gravity: >1

Solubility in water: Negligible

# 10. Stability and reactivity

Stability: Stable

Hazardous polymerization: Will not occur.

Hazardous thermal decomposition/

combustion byproducts:

None at room temperature. At extreme high temperatures (over 400°F), avoid inhaling

decomposition gases.

Conditions to avoid: Avoid extreme high temperatures (over 400°F) in

an enclosed area.

# 11. Toxicological information

**Product Information:** 

Acute Oral LD50: Unknown
Acute Dermal LD50: Unknown
Acute Inhalation LC50: Unknown
Ames Test: Unknown

# 12. Ecological information

Ecotoxicological information Unknown Chemical fate information: Unknown

#### 13. Disposal considerations

Disposal Method: Normal methods of disposal in accordance with any

governmental regulations.

#### 14. Transport information

DOT shipping name:
DOT Hazard Class:
Not known
DOT Label:
Not known
UN/NA Label:
Placards:
Not known

European Class:

RID (OCTf):

ADR (ECE):

Not known

RAR (IATA):

Not known

#### 15. Regulatory information

SARA Section 302:

SARA (311,312) Hazard Class:

Not known

SARA (313) Chemicals:

CPSC Classification:

WHMIS Hazard Class:

Harmonized Code:

Not known

Hazard Rating Systems:

HMIS: Not known NFPA: Not known

#### 16. Other

Users are advised to ensure that this information is brought to the attention of their employees handling the product. The information given herein is believed to be reliable. However, ADL Insulflex, Inc. makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. ADL Insulflex, Inc.'s obligations shall be only as set forth in ADL Insulflex, Inc.'s standard terms and conditions of sale for this product. In no case will ADL Insulflex, Inc. be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product.

Users of ADL Insulflex, Inc. products should make their own evaluation to determine the suitability of each such product for the specific application and to establish safe handling and installation procedures.

# Induction Melting Repairs Limited

Unit F, Bessemer Road, Attercliffe, Sheffield, South Yorkshire S9 3XN England

Tel: +44 (0)114 244 1001 24 Hours | Fax: +44 (0)114 244 1003 Email: sales@imr-ltd.co.uk | Website: www.imr-ltd.co.uk