

## Aerostyle Pyrojacket®

The world's most certified fire protection sleeve.



### Aerostyle Pyrojacket - Quick Facts

Custom colours available by special order.	
Sizes up to 5" (127mm) diameter.	
Continuous operating temp:	500°F (260°C)
Max short term exposure	3000°F (1650°C)
Molten splash resistance:	Outstanding
Flame resistance:	Very good
Abrasion resistance:	Very good
Flexibility	Outstanding
Water and oil resistance:	Outstanding



Proudly offering the following certifications and specifications:

- ✓ UL 1441 Certified
- ✓ VW1 Flame Test Certified
- ✓ MSHA Certified for use in underground mines
- ✓ SAE AS1072E
- ✓ GL – Germanischer Lloyd Certified for 800°C for 30 minutes
- ✓ BS EN 373 Molten Splash Tested
- ✓ BS EN 388 Abrasion Tested
- ✓ BS EN ISO 6940 Flame Resistance Tested
- ✓ BS EN ISO 6530 Oil Resistance Tested
- ✓ BS 2576 Tensile Strength Tested
- ✓ DIN 54837 / 5510-2 Rail Vehicle Certified for Resistance to Combustibility
- ✓ DIN 5659-2 / 5510-2 Rail Vehicle Certified for Toxicity

Distributed by:

**INDUCTION MELTING REPAIRS LTD.**

UNIT F, BESSEMER ROAD, ATTERCLIFFE, SHEFFIELD, SOUTH YORKSHIRE, ENGLAND, S9 3XN.

T: +44 (0)114 2441001

F: +44 (0)114 2441003

sales@imr-ltd.co.uk

www.imr-ltd.co.uk

**PYROJACKET®**